







BFDPPJ22 省エネ商品 YDP-100 つらいち枠 外倒し窓

|   |  |   |  |  |
|---|--|---|--|--|
| <p>外倒し窓(排煙窓)<br/>W=800 H=600</p>      | <p>外倒し窓連窓(排煙窓)<br/>W=1,700 H=600</p>      | <p>上段外倒し窓(排煙窓)、下段はめ殺し窓<br/>W=800 H=1,500</p>      |  |  |
| <p>外倒し窓(隠蔽式排煙窓)<br/>W=800 H=600</p>  | <p>外倒し窓連窓(隠蔽式排煙窓)<br/>W=1,700 H=600</p>  | <p>上段外倒し窓(隠蔽式排煙窓)、下段はめ殺し窓<br/>W=800 H=1,500</p>  |  |  |
|   |  |   |  | <p>YDP-100 外倒し窓 性能等級</p> <p>耐風圧性 S-5 (2400Pa)<br/>S-6 (2800Pa)<br/>S-7 (3600Pa)</p> <p>気密性 A-4 (2等級線)</p> <p>水密性 W-5 (500Pa)</p> <p>遮音性 T-2 (30等級線)</p> <p>断熱性 H-3 (0.287m<sup>2</sup>・K/W以上)<br/>(複層ガラス5+A12+5の場合)</p> <p>ただし、窓種・サイズにより適応値が異なります。</p> |