







BRDPPJ22 省エネ商品 YDP-100 RC枠 外倒し窓

<p>外倒し窓 (排煙窓)</p> <p>W=800 H=600</p> 	<p>外倒し窓連窓 (排煙窓)</p> <p>W=1,700 H=600</p> 	<p>上段外倒し窓 (排煙窓)、下段はめ殺し窓</p> <p>W=800 H=1,500</p> 		
<p>外倒し窓 (隠蔽式排煙窓)</p> <p>W=800 H=600</p> 	<p>外倒し窓連窓 (隠蔽式排煙窓)</p> <p>W=1,700 H=600</p> 	<p>上段外倒し窓 (隠蔽式排煙窓)、下段はめ殺し窓</p> <p>W=800 H=1,500</p> 		
				<p>YDP-100 外倒し窓 性能等級</p> <p>耐風圧性 S-5 (2400Pa) S-6 (2800Pa) S-7 (3600Pa)</p> <p>気密性 A-4 (2等級線)</p> <p>水密性 W-5 (500Pa)</p> <p>遮音性 T-2 (30等級線)</p> <p>断熱性 H-3 (0.287m²・K/W以上) (複層ガラス5+A12+5の場合)</p> <p>ただし、窓種・サイズにより適応値が異なります。</p>